

EE-214RY 2.1 inch E-paper Display

Opticon's EE-range are high resolution fully graphical, e-paper based displays. The display shows black, white, red and yellow colors. This ESL comes in 2.1 and 2.9 inch labels and has a high efficiency red LED.



Highlights

- Enables on-demand, real-time pricing, promotions and product information
- Reduces waste and labor costs and minimizes errors
- E-Paper display technology boasts a high contrast ratio and superior viewing angle
- High efficiency LED (red) to attract attention
- Complementary red and yellow color
- 100% display content flexibility and centralized administration of all devices and content via the Opticon ESL Server Software
- Bi-Stable display, so the image will remain on the display even after power is disconnected
- High contrast display allows scanning of barcodes off the display using a barcode scanner
- Display can be remotely updated via bidirectional communication using the Opticon Base Station
- A wide variety of secure, durable and esthetically pleasing display shelf mounting options and accessories for in-store shelving are available, for more information, check the Accessories brochure
- Extremely low power consumption
- 2.4 Ghz, 802.15.4 based protocol
- 250 x 122 pixels

EE-214RY

Product Specifications



Operation

CPU: 8051 8-bit MCU
Clock frequency: 32 MHz

Memory

Internal ROM: 96 KB
Internal RAM: 6 KB
External ROM: 512 KB

Operating indicators

Number of LEDs: 1, red
Buzzer: programmable frequency and volume

Communication

Range: typical 25 meter indoor; 100 meter open-field
Radio frequency: 2.4 GHz (2405 - 2480 MHz)
Radio transmission speed: up to 250 kbps
Protocol: IEEE 802.15.4 based
No. of EE-214RY ESL's per base station: 2,000

Power

Battery: 2x CR2450 Lithium primary batteries
Operating voltage 1.9-3.3V
Nominal voltage: 3.0V
Usable time: Approximately 5 years at room temperature, with 4 updates per day, no LED usage

Display

Size: 2.1", 250 x 122 pixels (WxH), black, white, red and yellow
Active area: 48.55 x 23.71 mm (WxH)
Contrast ratio: 8:1
Pixel Pitch: 130 dpi

Durability

Temperature in operation: 5 to 40 °C / 41 to 104 °F
Temperature in storage: -20 to 50 °C / -4 to 122 °F
Humidity in operation: 20 - 60% (non-condensing)
Humidity in storage: 20 - 60% (non-condensing)

Physical

Dimensions (WxHxD): 69.9 x 34.7 x 11.5 mm /
2.75 x 1.37 x 0.45 in
Weight: Ca. 45.0 g / 1.59 oz

Regulatory & safety

Product compliance: EN 60950-1:2006 +A11:2009+
A1:2010+A12:2011+A2:2013, IEC 60950-1:2005 (2nd
Edition)+Am 1:2009+Am 2:2013, EN55022: 2010,
EN55024: 2010, FCC, WEEE 2012/19/EU, RoHS
2011/65 EC

Accessories

For dedicated and universal accessories, check online the Accessories brochure of the EE-Range.